

FFSA Championnat de France Rallycross 2016 - 2018

Ref.	Dimensions	Type	Sec / Mouillé	Gomme	Diamètre Extérieur (mm)	Largeur bord à bord (mm)	Largeur BDR (mm)	Largeur de jante idéale (")	Largeurs de jante possibles (")	Poids (Kg)	Tours par KM
7811M	195/580-16	ACB11	Sec	A24	607	204	199	7,0	7.0 - 8.0	9,47	524
7802M	205/620-17	ACB11	Sec	A53	620	235	220	8,0	7.0 - 8.0	8,94	514
7805M	225/640-17	ACB11	Sec	A53	639	243	241	8,0	7.0 - 8.0	10,35	498
7806M	225/640-18	ACB11	Sec	A53	645	229	241	8,0	7.0 - 8.0	10,50	493
7808M	160/605R15	M+S	Pluie / Boue	A64	599	199	160	6,0	5.5 - 6.0	10,91	531
7809M	160/640R15	M+S	Pluie / Boue	A64	635	206	162	6,0	5.5 - 6.0	12,18	501
7810M	170/650R15	M+S	Pluie / Boue	A64	645	214	176	7,0	6.5 - 7.5	11,87	493
7807M	195/50R15	ZZR	Sec	A60	577	201	177	6,0	5.5 - 7.0	9,27	555
7812M	210/635R17	RXW	Pluie	W536	638	242	214	8,0	7.0 - 8.0	9,99	499

Catégorie	Type Voiture	Recommandations
-----------	--------------	-----------------

Super Car	2L 4WD	225/640-17 ACB11 225/640-18 ACB11
-----------	--------	--------------------------------------

Super 1600	1600 2WD	205/620-17 ACB11 225/640-17 ACB11 225/640-18 ACB11
------------	----------	--

Division 3	3.5L 4WD	195/580-16 ACB11
------------	----------	------------------

Division 4	2L 2WD	195/580-15 ACB11 195/580-16 ACB11 205/620-17 ACB11 215/580-15 ACB11 215/580-16 ACB11 225/640-17 ACB11 225/640-18 ACB11
------------	--------	--

Coupe Twingo	2WD 133-140cv	195/50R15 ZZR
--------------	---------------	---------------



ACB11



ZZR

M+S

RXW