

FFSA Championnat de France Rallycross 2019 - 2021

Ref.	Dimensions	Type	Sec / Mouillé	Gomme	Diamètre Extérieur (mm)	Largeur bord à bord (mm)	Largeur BDR (mm)	Largeur de jante idéale (")	Largeurs de jante possibles (")	Poids (Kg)	Tours par KM
8294M	195/580-16	ACB11	Sec	A30	607	204	199	7,0	7.0 - 8.0	9,47	524
8295M	205/620-17	ACB11	Sec	A53	620	235	220	8,0	7.0 - 8.0	8,94	514
8296M	225/640-17	ACB11	Sec	A53	639	243	241	8,0	7.0 - 8.0	10,35	498
8297M	225/640-18	ACB11	Sec	A53	645	229	241	8,0	7.0 - 8.0	10,50	493
8298M	160/605R15	M+S	Pluie / Boue	A64	599	199	160	6,0	5.5 - 6.0	10,91	531
8299M	160/640R15	M+S	Pluie / Boue	A64	635	206	162	6,0	5.5 - 6.0	12,18	501
8300M	170/650R15	M+S	Pluie / Boue	A64	645	214	176	7,0	6.5 - 7.5	11,87	493
8301M	195/50R15	RS3-R	Sec	A60	577	201	177	6,0	5.5 - 7.0	9,27	555
8302M	210/635R17	RXW	Pluie	W536	638	242	214	8,0	7.0 - 8.0	9,99	499

Catégorie	Type Voiture	Recommandations	
Super Car	2L 4WD	225/640-17 225/640-18	ACB11 ACB11
Super 1600	1600 2WD	205/620-17 225/640-17 225/640-18	ACB11 ACB11 ACB11
Division 3	3.5L 4WD	195/580-16	ACB11
Division 4	2L 2WD	195/580-16 205/620-17 225/640-17 225/640-18	ACB11 ACB11 ACB11 ACB11
Coupe Twingo	2WD 133-140cv	195/50R15	RS3-R

